

Datasheet | Abrasives

PEENOX® PERFORM+

LONGLIFE CARBON STEEL CUT WIRE SHOT FOLLOWING VDFI

GENERAL INFORMATION APPLICATIONS Abrasive Carbon steel cut wire shot Shot peening and peen forming Conditioned Shape CHEMICAL COMPOSITION **SIZES C** 0.70 – 0.78 % (610 – 670 HV1) 0.10 - 0.30%0.30 mm | 0.012" | 0.50 mm | 0.020" | 0.80 mm | 0.032" | 1.20 mm | 0.047" 0.50 - 0.80 % 0.70-0.78% (640-700 HV1) 0.35 mm | 0.014" | 0.60 mm | 0.023" | 0.90 mm | 0.035" 0.80 - 0.88 % (670 - 730 HV1) S, P max. 0.030% 0.40 mm | 0.017" | 0.70 mm | 0.028" | 1.00 mm | 0.041" MODE OF USE PHYSICAL PROPERTIES Reusable blasting medium Structure Tempered SHOT BLASTING SYSTEMS Hardness 610-670 HV1 (56-59 HRC) Blasting wheel and compressed air 640 - 700 HV1 (57 - 60 HRC) **CERTIFICATIONS & SYSTEM APPROVAL** 670-730 HV1 (59-61 HRC) 770 - 830 HV1 (63 - 65 HRC) VDFI 8001, (DIN 8201-4) Standards Specific weight ca. 7.8 g/cm3 Certifications ISO 9001 **Bulk** weight ca. 4.6 kg/l **GRADES** G1 Conditioned (ccw) G3 Spherically conditioned (sccw) G2 Double conditioned (DCCW) Subject to change without notice. All specification are only a general description of our products. For detailed information please ask for our product leaflets.

INFO

PEENOX® PERFORM+ is a longlife carbon steel cut wire shot for shot peening und peen forming. It is made from carbon steel wire of selected diameter and tensile strength by means of special cutting machines. The material is specially tempered. It is the preliminary stage of conditioned cut wire pellets and fulfils the specification VDFI 8001 of the "Verband der Deutschen Federnindustrie e.V.".

PACKAGING



25 kg (55 lbs) 1,000 kg (2,205 lbs) per pallet (= 40 bags)



Big Bag 1,000 kg (2,205 lbs)



Drum 907 kg (2,000 lbs)





Keep Dry

