



# KRAMPE HAREX®

## KNOW WHY.

### Data Sheet | Fibres

Version 05/2019

## SYNTHETIC FIBRE FIBRILLATED SYNTHETIC FIBRE

1 Type of fibre 3 Length

# PFF 6/60

2 Shape of fibre

4 Width



w

L

#### GEOMETRY

1 Type of fibre	synthetic fibre
2 Shape of fibre	Fibrillated synthetic fibre
3 Length (L)	6 mm
4 Width (w)	60 µm
Cross section	angular cross section, fine fibrillated
Ratio (L/d)	

#### FIBRE NETWORK

Quantity of fibres	- fibres/kg
Minimum dosage	- kg/m <sup>3</sup>

#### MATERIAL PROPERTIES

Material specifications	Fibrillated synthetic fibre
Material	Polypropylene
Material number	-
Tensile strength	≥ 300 N/mm <sup>2</sup>
Modulus of elasticity	~ 1.300-1.800 N/mm <sup>2</sup>

#### CERTIFICATIONS & SYSTEM APPROVALS

Standards (DIN)	EN 14889-2
Certifications (DIN)	EN ISO 9001:2015, EN ISO 50001



Subject to change without notice. All specifications are only a general description of our products. For detailed information please ask for our product leaflets.

#### INFO

Krampe Harex® Fibres are a cost effective solution to conventional reinforcement methods.:

- > Industrial floors
- > Tunneling applications
- > Precast concrete elements
- > Applications in residential buildings

In relation to our **Service+** offer, we determine the suitable type of fibre, the optimal dosage and the necessary concrete strength. Further information can be found on our website [krampeharex.com](http://krampeharex.com).

#### PACKAGING



Bags



Boxes\*



Big Bag

#### STORAGE



Keep Dry

\* Fibres are magnetically linearized.